



NEW PRODUCT LAUNCHING



Valid until 30th September 2023

* WHILE STOCKS LAST, LIMITED AVAILABILITY

GA048G


Excellent maneuverability

the motor housing is designed as slim as possible allowing for a variety of gripping options² to provide excellent maneuverability.

²User can grip the tool with his/ her thumb or fingers placed not only on the main handle but also on the motor housing.



No Load Speed
11,000
min⁻¹



Slide lever style wheel cover



Anti-restart function



Electric brake

Integrated Drum Type Motor Housing



Anti-vibration construction
Rubber damper is located between Motor Housing and Main handle.

GA048GZ 100 mm (4")

Cordless Angle Grinder

• High work efficiency that exceeds the competing models has been achieved by using "Highly rigid, integrated drum type motor housing" and "Anti-vibration construction" to be compatible with high-speed BL motor



Li-ion Ah 8.0 | 5.0 | 4.0 | 2.5 | 2.0

40Vmax *Recommended batteries 2.5Ah, 4.0Ah, 5.0Ah

Paddle Switch



Standard Equipment:

Wheel Cover, Cutting Wheel Cover Attachment, Vibration Proof Grip, Lock Nut Wrench 20, Grinding Wheel 100X6X16 (A-80852)

• GZ: Without Charger & Battery



XGT BL MOTOR AFT XPT

Wheel Diameter	100mm (4")
Max Abrasive Wheel Thickness	6.4mm (1/4")
Hole Diameter	16mm (5/8")
Cutting Depth	21mm (13/16")
No Load Speed (RPM)	11,000
Dimensions (L x W x H)	343x117x144mm (13-1/2x4-5/8x5-5/8")
Net weight	2.8 - 5.2kg (6.2 - 11.5lbs.)
Work Amount (approx.)	8 cuts with BL4040, Concrete Cutting 20 mm depth x 600 mm width with Diamond Wheel

JV001GZ

Cordless Jig Saw

• Higher user-friendliness has been achieved by adding light reduction function, redesigning tool body shape and more



Li-ion Ah 8.0 | 5.0 | 4.0 | 2.5 | 2.0

40Vmax *Recommended batteries 2.0Ah, 2.5Ah, 4.0Ah



Standard Equipment:

Anti-Splitting Device, Hex Wrench 4, Jig Saw Blade Set (No. BR-10, BR-13, B-22, 2pcs each)

• GZ: Without Charger & Battery



XGT BL MOTOR SOFT NOLOAD XPT

Max output	700W
Capacity	Wood: 135mm (5-5/16") Mild steel: 10mm (3/8") Aluminum: 20mm (13/16")
Length of Stroke	26mm (1")
Strokes Per Minute (SPM)	800 - 3,500
Shank type	Saw blade: Bayonet Shank Jig Saw Blade
Bevel range	0 - 45°
Dimensions (L x W x H)	269x84x189mm (10-5/8x3-5/16x7-7/16")
Net weight	2.6 - 2.9kg (5.7 - 6.4lbs.)
Work Amount (approx.)	230 pcs with BL4040, sawing with Blade B-10 with max orbital mode MDF Thickness 24 mm x width 300 mm

DDF489RTJ | DDF489Z 13 mm (1/2")

Cordless Driver Drill

• Mechanical 2-speed gearing; High speed mode for speedy drilling in light duty applications; Low speed mode for heavy duty applications requiring high torque



Li-ion Ah 6.0 | 5.0 | 4.0 | 3.0 | 2.0 | 1.5

18V



2 modes



Standard Equipment:

Hook, + Bit

• RTJ: 1x Rapid Charger, 2x 5.0Ah Battery, 1x Connector Plastic Case (Type 2)

• Z: Without Charger & Battery



XGT BL MOTOR XPT

Capacity	Steel: 13mm (1/2") Wood (Drill bit): 1-1/2mm (3/8") Wood (Auger-Bit) Flat bit/ Formwork Forstner drill bit Ship auger Single spur auger bit: 38mm (1-1/2") Wood (Self-feed bit) Hole saw: 51mm (2") Siding board Multi-siding core bit: 70mm (2-3/4") Adjustable circle: 120mm (4-3/4") Brush flap wheel: 100mm (3-15/16") Glass: 12mm (15/32") Step/cone drill: 32mm (1-1/4")
Chuck Capacity	1.5 - 13mm (1/16 - 1/2")
No Load Speed (RPM)	High: 0 - 1,800 Low: 0 - 550
Max Fastening Torque	Hard: 73N·m (650in.lbs.) Soft: 40N·m (350in.lbs.)
Max Lock Torque	80N·m (700in.lbs.)
Dimensions (L x W x H)	174x81x213mm (6-7/8x3-3/16x8-3/8")
Net weight	1.8 - 2.5kg (4.0 - 5.5lbs.)
Work Amount (approx.)	185 holes with BL1850B, ship Auger-Bit Ø 7/8" (2 x 38 mm thick SPF wood), high speed