

Makita®

NEW

15% OFF

*FOR TOOLS ONLY

PRODUCT LAUNCHING

Valid until 30th September 2026

* WHILE STOCKS LAST, LIMITED AVAILABILITY

HS014G 40Vmax Cordless Circular Saw



Blade Diameter	125 mm (4-7/8")
Max Cutting Capacity	0°: 47 mm (1-7/8") 45° right: 30 mm (1-3/16") 15° left: 20 mm (13/16")
No Load Speed (RPM)	6,400
Work Amount (approx.)	257 cuts with BL4040F Melapi thickness 45 mm width 300 mm Bevel angle 0°

BL MOTOR AWS XPT AFT ADT

Max Cutting
Depth
47 mm



Max Cutting
Depth
20 mm
15° left





Blower function & LED Job light
LED Job light with preglow and afterglow functions.



Safety cover open lever
When it is necessary to raise the safety cover, such as for flush cutting, the cover can be opened by manual operation using the lever.

10% OFF Accessory (Optional)

EFFICUT T.C.T. saw blade
125 mm x 25T
Part No. E-28880
125 mm x 45T
Part No. B-69462



Remove the
sub-base
when making
flush cuts

ML014G 40Vmax 18V

Cordless Tower Light

Luminous Flux	1,100 - 15,000 lm
Illuminance	at 1 m from the light source: 400 - 5,000 lx at 5 m from the light source: 16 - 200 lx
LED Type	Color: Daylight white Color temperature: 5,000 K
Brightness Setting	Stepless (Dial)
Continuous Usage Time (approx.)	3.6 - 48 hrs with BL4080F + BL18120



Adjustable light angle

The light angle is easily adjustable to suit your application, providing optimal illumination.

The light head rotates 180°



Light base rotates 180°



Max Luminous Flux
15,000 lm


Anti-Tipping Design
To prevent accidental tipping



Manually adjustable height
Easy tripod setup by slide handle

Lightweight
9.5 kg
tool only

Excellent portability
Lightweight Body & Integrated Tripod



Stepless brightness settings
15,000 lumens - 1,100 lumens

Max Height
2.4 m



Up to two battery can be installed:
Only one XGT or 18V LXT Two;
One XGT and One 18V LXT in parallel connection

HB351 Magnetic Drill



Continuous Rating Input	1,050 W
Cutting Capacity Diameter	35 mm (1-3/8")
Cutting Capacity Depth	50 mm (2")
Stroke Length	168 mm (6-5/8")
No Load Speed (RPM)	790
Magnetic Clamping Force	11,000 N



Cutting Capacity Diameter
35 mm
HB351

Developed specially for drilling holes in ferrous materials

HB501 Magnetic Drill



Continuous Rating Input	1,200 W
Cutting Capacity Diameter	50 mm (2")
Cutting Capacity Depth	50 mm (2")
Stroke Length	70 mm (2-3/4")
No Load Speed (RPM)	450 / 750
Magnetic Clamping Force	12,000 N



Cutting Capacity Diameter
50 mm
HB501

Powerful magnetic drilling for steel and other ferrous metals

10% OFF Accessory (Optional)

T.C.T Cutter
Cutting Depth 35 mm



T.C.T Cutter
Cutting Depth 50 mm



Diameter mm	Part No.	Diameter mm	Part No.
12	B-90641	26	B-90716
14	B-90657	28	B-90722
16	B-90663	32	B-90738
18	B-90679	36	B-90744
20	B-90685	40	B-90750
22	B-90691	50	B-90766
24	B-90700		

Diameter mm	Part No.	Diameter mm	Part No.
12	B-90772	26	B-90847
14	B-90788	28	B-90853
16	B-90794	32	B-90869
18	B-90803	36	B-90875
20	B-90819	40	B-90881
22	B-90825	50	B-90897
24	B-90831	64	B-90906