

## Cordless Jig Saw series

	Top Handle	Barrel Handle
40V max	JV002G 	JV001G 
18V	DJV182  DJV184 	DJV181  DJV185 
12V max	JV103D 	JV102D 

### JV002GZ

#### Cordless Jig Saw

- 40Vmax XGT BL cordless top handle Jig Saw, 3 orbital settings plus straight cutting, twin LED lights.



Li-ion Ah 8.0 | 5.0 | 4.0 | 2.5 | 2.0  
\*Recommended batteries  
2.0Ah, 2.5Ah, 4.0Ah, 4.0Ah (F)  
40Vmax



Standard Equipment:  
Dust Nozzle Assembly (122C71-6), Kerf Board (415524-7),  
Hex Wrench (783202-0), Jig Saw Blade Set (No. B10, B22, BR13)

- GZ: Without Charger & Battery



Max Output	800 W
Capacity	Wood: 135 mm (5-5/16")   Mild steel: 10 mm (3/8") Aluminum: 20 mm (13/16")
Length of Stroke	26 mm (1")
Strokes Per Minute (SPM)	0 - 3,500
Bevel Range	0 - 45°
Dimensions (L x W x H)	272 x 84 x 208 mm (10-3/4 x 3-5/16 x 8-3/16")
Net Weight	2.7 - 3.0 kg (6.0 - 6.6 lbs)
Work Amount (approx.)	186 pcs with BL4025 sawing with Blade B-10, max orbital mode MDF Thickness 24 mm x width 300 mm

### JV001GZ

#### Cordless Jig Saw

- Higher user-friendliness has been achieved by adding light reduction function, redesigning tool body shape and more.



Li-ion Ah 8.0 | 5.0 | 4.0 | 2.5 | 2.0  
\*Recommended batteries  
2.0Ah, 2.5Ah, 4.0Ah, 4.0Ah (F)  
40Vmax



Standard Equipment:  
Anti-Splintering Device, Hex Wrench 4, Jig Saw Blade Set  
(No. BR-10, BR-13, B-22, 2pcs each)

- GZ: Without Charger & Battery



Max Output	700 W
Capacity	Wood: 135 mm (5-5/16") Mild steel: 10 mm (3/8") Aluminum: 20 mm (13/16")
Length of Stroke	26 mm (1")
Strokes Per Minute (SPM)	800 - 3,500
Bevel Range	0 - 45°
Dimensions (L x W x H)	269 x 84 x 189 mm (10-5/8 x 3-5/16 x 7-7/16")
Net Weight	2.6 - 2.9 kg (5.7 - 6.4 lbs)
Work Amount (approx.)	230 pcs with BL4040, sawing with Blade B-10 with max orbital mode MDF Thickness 24 mm x width 300 mm

Like us on Facebook  
**MAKITA MALAYSIA**

• Continuous Usage Time/ Work Amount: Actual performance may vary based on application. Items of standard equipment and specifications may vary by country or area. The weight and dimensions may differ depending on the attachment(s), including the battery cartridge. All pictures shown are for illustration purposes only.

Makita Power Tools (Malaysia) Sdn. Bhd. Co. Registration No.: 201301001778 (1031615-M)

HQ & Service Centre  
Lot 824, Jalan Subang 5, Subang Industrial Area,  
47500 Subang Jaya, Selangor.  
Tel: 03-8023 0824 (General) | Fax: 03-8022 1448  
03-8022 1443 (Service)

Johor (Johor Bahru) Service Centre  
No. 12 & 14, Jalan Rosmerah 2/9,  
Taman Johor Jaya,  
81100 Johor Bahru, Johor.  
Tel: 07-364 9406 | Fax: 07-364 9407

Sarawak (Kuching) Service Centre  
Lot 1227, Lorong Demak Indah 2A,  
Demak Laut Industrial Area, Phase 2A,  
93050 Kuching Sarawak.  
Tel: 082-496 800 | Fax: 082-496 900

Sabah (Kota Kinabalu) Service Centre  
Lot 19, Jalan Buah Duku,  
Kolombong Light Industrial Estate, Off Jalan Kolombong,  
Kolombong Zone 1, 88450 Inanam, Kota Kinabalu, Sabah.  
Tel: 088-388 278 | Fax: 088-388 279

**12 MONTHS WARRANTY**



www.makita.my  
makita@makita.my

**Makita**

Cordless Jig Saw  
JV002G / JV001G

**XGT**

**XGT**  
**40V Li-ion max**

JV002G



PRODUCT  
DETAILS  
Models and specs  
may vary by country

JV001G



PRODUCT  
DETAILS  
Models and specs  
may vary by country

Cutting speed  
**20% up**

Compared to predecessor 18V model

Top Handle  
JV002G



Barrel Handle  
JV001G



**BL SOFT XPT MOTOR NOLOAD**

# High power

**BL MOTOR**



# Constant speed control

XGT technology and constant speed control reduce the chance of drop in cutting speed, providing excellent cutting performance higher than our current and competing models in a wide range of applications from thin metal cutting to 48mm thick MDF cutting.

## Top Handle JV002G



**Lock-off button**

**Variable speed control by trigger**  
allows for easier precise alignment of the blade with pencil line.



## Barrel handle JV001G



**Electronic push button switch**  
located on both sides of Housing



### 3 Orbital settings + Straight cutting



Optimum cutting action can be selected by simply turning the change lever.

Position	Cutting action	Applications
0	Straight line cutting	Cuts in mild steel, stainless steel and plastics Clean cuts in wood and plywood
I	Small orbital cutting	Cuts in mild steel, aluminum and hard wood
II	Medium orbital cutting	Cuts in wood and plywood Fast cuts in aluminum and mild steel
III	Large orbital cutting	Fast cuts in wood and plywood

### Variable speed control by dial



photo:  
JV002G

Number	Workpiece
4 - 6	Wood
3 - 6	Mild steel
3 - 4	Stainless steel
3 - 6	Aluminum
1 - 4	Plastics

### Toolless blade clamp



with a blade holder which allows for one-hand blade change

### LED job light




(Twin LEDs with light up function during standby mode)

### Light reduction function

- Less glare when cutting metal
- Press and hold the main power button for 3 brightness settings.
- Memory function: The tool remembers the job light brightness set last time and the light will light up at that brightness when turned on.

### Dust Collection



Front cuff 24 (option)

Dust nozzle can be set to Base firmly with Thumb screw.

Dust nozzle can be attached over the sawdust exhaust port for connection to Makita vacuum cleaner.

### SOFT NOLOAD New Soft no-load

- Easy, precise alignment of blade with pencil line at cut starting point
- With disabling function
- If the tool detects no-load motor rotation during intermittent operation such as precision cut-out, it switches automatically back to Soft no-load mode.

### Bevel range

0 to 45° left and right.



### Less wobbling

Improved stability during cutting due to a wider base plate

**XPT**  
Extreme Protection Technology