



**Cordless Hammer Driver Drill
Cordless Driver Drill
DHP489 / DDF489 13 mm (1/2")**



**Cordless Hammer
Driver Drill
DHP489**



**Cordless
Driver Drill
DDF489**



Max Lock Torque

80 N·m



Excellent drilling capacity

with up to 1" ship auger bit in high speed mode



DHP489



DDF489

Mechanical 2-speed



Robust keyless drill chuck with single metal sleeve

Excellent maneuverability (DHP489 only)

Despite increased efficiency, the overall length is shorter than that of our current model due to optimally redesigned gear assembly.



Twin LED job light



with preglow and afterglow functions

Variable speed control by trigger



Accessories (optional)

Hook

For BL1815N / BL1820B
Part No. 346449-3

For BL1830B / BL1840B
/ BL1850B / BL1860B
Part No. 346317-0



DHP489RTJ | DHP489Z 13 mm (1/2")

Cordless Hammer Driver Drill

• Variable 2-speed for a wide range of drilling, fastening and hammer drilling applications.



18V



Standard Equipment:

Hook, (+)(-) Bit

- RTJ: 1x Rapid Charger, 2x 5.0Ah Battery, 1x Makpac Connector Box Type 2
- Z : Without Charger & Battery



Capacity	Masonry: 16 mm (5/8") Steel: 13 mm (1/2") Wood (Auger-bit): 38 mm (1-1/2") Wood (Self-feed bit): 51 mm (2") Wood (Hole saw): 51 mm (2") Siding board: 70 mm (2-3/4")
Chuck Capacity	1.5 - 13 mm (1/16 - 1/2")
Impacts Per Minute (IPM)	High: 0 - 27,000 Low: 0 - 8,250
No Load Speed (RPM)	High: 0 - 1,800 Low: 0 - 550
Max Fastening Torque	Hard: 73 N·m (650 in lbs) Soft: 40 N·m (350 in lbs)
Max Lock Torque	80 N·m (700 in lbs)
Max Output	620 W
Dimensions (L x W x H)	175 x 81 x 261 mm (6-7/8 x 3-3/16 x 10-1/4")
Net Weight	1.8 - 2.5 kg (4.0 - 5.5 lbs)
Work Amount (approx.)	185 holes with BL1850B Ship Auger-Bit Ø 7/8", high speed (2 x 38 mm thick SPF wood)

DDF489RTJ | DDF489Z 13 mm (1/2")

Cordless Driver Drill

• Mechanical 2-speed gearing; High speed mode for speedy drilling in light duty applications; Low speed mode for heavy duty applications requiring high torque.



18V



Standard Equipment:

Hook, (+)(-) Bit

- RTJ: 1x Rapid Charger, 2x 5.0Ah Battery, 1x Makpac Connector Box Type 2
- Z : Without Charger, Battery & Carrying Case



Capacity	Steel: 13 mm (1/2") Wood (Auger-Bit): 38 mm (1-1/2") Wood (Hole Saw): 51 mm (2")
Chuck Capacity	1.5 - 13 mm (1/16 - 1/2")
No Load Speed (RPM)	High: 0 - 1,800 Low: 0 - 550
Max Fastening Torque	Hard: 73 N·m (650 in lbs) Soft: 40 N·m (350 in lbs)
Max Lock Torque	80 N·m (700 in lbs)
Dimensions (L x W x H)	174 x 81 x 213 mm (6-7/8 x 3-3/16 x 8-3/8")
Net Weight	1.8 - 2.5 kg (4.0 - 5.5 lbs)
Work Amount (approx.)	185 holes with BL1850B, ship Auger-Bit Ø 7/8" 2 x 38 mm thick SPF wood, high speed

Like us on Facebook
MAKITA MALAYSIA

• Continuous Usage Time/ Work Amount: Actual performance may vary based on application. Items of standard equipment and specifications may vary by country or area. The weight and dimensions may differ depending on the attachment(s), including the battery cartridge. All pictures shown are for illustration purposes only.

Makita Power Tools (Malaysia) Sdn. Bhd. Co. Registration No.: 201301001778 (1031615-M)

HQ & Service Centre

Lot 824, Jalan Subang 5, Subang Industrial Area, 47500 Subang Jaya, Selangor.
Tel: 03-8023 0824 (General) | Fax: 03-8022 1448
03-8022 1443 (Service)

Johor (Johor Bahru) Service Centre

No.12 & 14, Jalan Rosmerah 2/9, Taman Johor Jaya, 81100 Johor Bahru, Johor.
Tel: 07-364 9406 | Fax: 07-364 9407

Sarawak (Kuching) Service Centre

Lot 1227, Lorong Demak Indah 2A, Demak Laut Industrial Area, Phase 2A, 93050 Kuching Sarawak.
Tel: 082-496 800 | Fax: 082-496 900

Sabah (Kota Kinabalu) Service Centre

Lot 19, Jalan Buah Duku, Kolombong Light Industrial Estate, Off Jalan Kolombong, Kolombong Zone 1, 88450 Inanam, Kota Kinabalu, Sabah.
Tel: 088-388 278 | Fax: 088-388 279

12 MONTHS WARRANTY



www.makita.my
✉ makita@makita.my