



Cordless Impact Wrench

TW001G 19 mm (3/4")

TW002G 12.7 mm (1/2")



40V Li-ion max

Over 2,000 N·m of Nut-Busting Torque



VIDEO CLIP

Models and specs may vary by country



TW001G



PRODUCT DETAILS
Models and specs may vary by country



TW002G



PRODUCT DETAILS
Models and specs may vary by country

TW001G

Max fastening torque

1,800N·m

Nut-busting torque

2,050N·m

19 mm (3/4")

Square drive



TW002G

Max fastening torque

1,700N·m

Nut-busting torque

2,200N·m

12.7 mm (1/2")

Square drive



TW001G

19mm (3/4") Square drive, C ring

TW002G

12.7mm (1/2") Square drive, C ring (without hole)



Twin LED job light



Electric 4-stage impact power selection

enables user to control the power and speed depending on the applications.



Mode	No load speed (min ⁻¹)		Impacts per minutes (min ⁻¹)	
	TW001G	TW002G	TW001G	TW002G
1. Soft	0-950	0-850	0-1,900	0-1,700
2. Med.	0-1,150	0-900	0-2,200	0-1,800
3. Hard	0-1,400	0-1,000	0-2,400	0-2,000
4. Max.	0-1,800	0-1,800	0-2,500	0-2,400

Full speed mode

Switches between variable and full speed by pressing the button. Reaches full speed with fewer pull trigger to minimize user's fatigue in continuous work.

Compact overall length for easy handling and control



Our 18V model

Forward and reverse rotation auto stop mode

With constant speed control (except Max. mode)



Mode	Forward	Reverse
1. Soft	Stops immediately after impact is detected	Stops immediately after the bolt/ nut gets loosened
2. Med.	Stops approximately 0.5 seconds after impact is detected	Stops approximately 0.2 seconds after the bolt/ nut gets loosened
3. Hard	Stops approximately 1 second after impact is detected	Shift to 230 min ⁻¹ after the bolt/ nut gets loosened

Accessories (optional)

Extension handle set

Part No. 191G67-2



TW001GM204 | TW001GZ02 | TW001GZ 19 mm (3/4")

Cordless Impact Wrench

Higher torque but compact overall length for easy handling and control.



Li-ion Ah 8.0 | 5.0 | 4.0 | 2.5 | 2.0

*Recommended batteries 2.0Ah, 2.5Ah, 4.0Ah, 4.0Ah (F) 40Vmax

Standard Equipment:

Belt Clip, Shoulder Belt (161347-8) for GM204 & GZ02

- GM204 : 1x Fast Charger, 2x 4.0Ah Battery, 1x Makpac Connector Box Type 3
- GZ02/ GZ: Without Charger, Battery & Carrying Case



BL MOTOR XPT



Fastening Capacities	Standard Bolt: M12 - M36 (1/2" - 1-7/16") High Strength Bolt: M10 - M27 (3/8" - 1-1/16")
Square Drive	19 mm (3/4"), C-ring
No Load Speed (RPM)	Max: 0 - 1,800 Hard: 1,400 Mid: 1,150 Soft: 950
Impacts Per Minute (IPM)	Max: 0 - 2,500 Hard: 2,400 Mid: 2,200 Soft: 1,900
Max Fastening Torque	1,800 N·m (1,330 ft lbs)
Nut-Busting Torque	2,050 N·m (1,510 ft lbs)
Dimensions (L x W x H)	217 x 94 x 297 mm (8-1/2 x 3-11/16 x 11-3/4")
Net Weight	3.9 - 4.2 kg (8.6 - 9.3 lbs)
Work Amount (approx.)	870 pcs with BL4040 x2 Tightening of M24 bolts

TW002GM201 | TW002GZ 12.7 mm (1/2")

Cordless Impact Wrench

Making the tool suitable for tasks such as chassis maintenance and construction site work.



Li-ion Ah 8.0 | 5.0 | 4.0 | 2.5 | 2.0

*Recommended batteries 2.0Ah, 2.5Ah, 4.0Ah, 4.0Ah (F) 40Vmax

Standard Equipment:

Hook

- GM201: 1x Fast Charger, 2x 4.0Ah Battery, 1x Makpac Connector Box Type 3
- GZ : Without Charger, Battery & Carrying Case



BL MOTOR XPT



Square Drive	12.7 mm (1/2")
No Load Speed (RPM)	Max: 0 - 1,800 Hard: 1,000 Mid: 900 Soft: 850
Impacts Per Minute (IPM)	Max: 0 - 2,400 Hard: 2,000 Mid: 1,800 Soft: 1,700
Max Fastening Torque	1,700 N·m (1,250 ft lbs)
Nut-Busting Torque	2,200 N·m (1,620 ft lbs)
Dimensions (L x W x H)	213 x 94 x 297 mm (8-3/8 x 3-11/16 x 11-3/4")
Net Weight (with battery)	3.9 - 5.1 kg (8.6 - 11.2 lbs)

Like us on Facebook
MAKITA MALAYSIA

*Continuous Usage Time/ Work Amount: Actual performance may vary based on application. Items of standard equipment and specifications may vary by country or area. The weight and dimensions may differ depending on the attachment(s), including the battery cartridge. All pictures shown are for illustration purposes only.

12 MONTHS WARRANTY



www.makita.my
makita@makita.my

Makita Power Tools (Malaysia) Sdn. Bhd. Co. Registration No.: 201301001778 (1031615-M)

HQ & Service Centre

Lot 824, Jalan Subang 5, Subang Industrial Area, 47500 Subang Jaya, Selangor
Tel: 03-8023 0824 (General) | Fax: 03-8022 1448
03-8022 1443 (Service)

Johor (Johor Bahru) Service Centre

No. 12 & 14, Jalan Rosmerah 2/9, Taman Johor Jaya,
81100 Johor Bahru, Johor.
Tel: 07-364 9406 | Fax: 07-364 9407

Sarawak (Kuching) Service Centre

Lot 1227, Lorong Demak Indah 2A, Demak Laut Industrial Area, Phase 2A, 93050 Kuching Sarawak.
Tel: 082-496 800 | Fax: 082-496 900

Sabah (Kota Kinabalu) Service Centre

Lot 19, Jalan Buah Duku, Kolombong Light Industrial Estate, Off Jalan Kolombong, Kolombong Zone 1, 88450 Inanam, Kota Kinabalu, Sabah.
Tel: 088-388 278 | Fax: 088-388 279