

One-touch bit installation

Smoother installation of the bit has been achieved by reducing the resistance against insertion of the bit.

Anti-bit wobbling structure

One LED job light each on both sides

Light mode
 • To turn on the light, set F/R change lever in the neutral position, then pull the switch trigger. To turn off the light, pull the switch trigger again.
 • The light turns off automatically one hour after turned on.



Constant speed control

Allows to operate the tool at the same speed as that at which you operate the tool on a full charged battery, even when the remaining battery capacity becomes low.

Simple impact power selection

Mode	Rotation direction	Assist function
4 modes (for bolt)	Forward	Stops the machine approx 0.2 seconds after it has stopped impact blows.
	Reverse	No
T-mode (for thin metal only)	Forward	No
	Reverse	Stops the machine at the same time as impact blow is detected.



4 modes (Max/ Hard/ Med. / Soft for bolt)
1 T-mode (for thin metal only)



BL MOTOR XPT

TD003GA201 | TD003GZ

Cordless Impact Driver

40Vmax



*Recommended batteries
2.0Ah, 2.5Ah, 4.0Ah, 4.0Ah (F)



Standard Equipment:
Belt Clip

- GA201: 1x Standard Charger, 2x 2.0Ah Battery, 1x Makpac Connector Box Type 2
- GZ : Without Charger, Battery & Carrying Case



Capacity	Machine Screw: M4 - M8 (5/32 - 5/16") Standard Bolt: M5 - M16 (3/16 - 5/8") High Strength Bolt: M5 - M14 (3/16 - 9/16") Coarse Thread (in length): 22 - 125 mm (7/8 - 4-7/8") Steel: 22 mm (7/8") Wood (Auger Bit): 24 mm (15/16") 6.35 mm (1/4")
Hex Shank	6.35 mm (1/4")
No Load Speed (RPM)	Max / Hard / Med. / Soft / T mode: 0 - 3,700 / 0 - 3,200 / 0 - 2,100 / 0 - 1,100 / 0 - 2,400
Impacts Per Minute (IPM)	Max / Hard / Med. / Soft / T mode: 0 - 4,100 / 0 - 3,600 / 0 - 2,600 / 0 - 1,400 / N/A
Max Fastening Torque	210 N·m (1,860 in lbs)
Dimensions (L x W x H)	121 x 86 x 245 mm (4-3/4 x 3-3/8 x 9-5/8")
Net Weight	1.7 - 2.9 kg (3.7 - 6.4 lbs)
Work Amount (approx.)	280 pcs with BL4025 Coarse thread screw 120 mm

Like us on Facebook
MAKITA MALAYSIA

*Continuous Usage Time/ Work Amount: Actual performance may vary based on application. Items of standard equipment and specifications may vary by country or area. The weight and dimensions may differ depending on the attachment(s), including the battery cartridge. All pictures shown are for illustration purposes only.

Makita Power Tools (Malaysia) Sdn. Bhd. Co. Registration No.: 201301001778 (1031615-M)

HQ & Service Centre
Lot 824, Jalan Subang 5, Subang Industrial Area,
47500 Subang Jaya, Selangor.
Tel: 03-8023 0824 (General) | Fax: 03-8022 1448
03-8022 1443 (Service)

Johor (Johor Bahru) Service Centre
No.12 & 14, Jalan Rosmerah 2/B,
Taman Johor Jaya,
81100 Johor Bahru, Johor.
Tel: 07-364 9406 | Fax: 07-364 9407

Sarawak (Kuching) Service Centre
Lot 1227, Lorong Demak Indah 2A,
Demak Laut Industrial Area, Phase 2A,
93050 Kuching Sarawak.
Tel: 082-496 800 | Fax: 082-496 900

Sabah (Kota Kinabalu) Service Centre
Lot 19, Jalan Buah Duku,
Kolombong Light Industrial Estate, Off Jalan Kolombong,
Kolombong Zone 1, 88450 Inanam, Kota Kinabalu, Sabah.
Tel: 088-388 278 | Fax: 088-388 279



www.makita.my
makita@makita.my

Max fastening torque
210
N·m



PRODUCT DETAILS
Models and specs may vary by country.

Work amount on a full battery charge BL4025

approx **280** pcs.

Drove 120mm coarse thread screws into melapi.



**BL
MOTOR**

Aluminum hammer case

One-touch bit installation

Smoother installation of the bit has been achieved by reducing the resistance against insertion of the bit.

Anti-bit wobbling structure



Max fastening torque
210
N·m



Simple impact power selection

Mode	Rotation direction	Assist function
4 modes (for bolt)	Forward	Stops the machine approx 0.2 seconds after it has stopped impact blows.
	Reverse	No
T-mode (for thin metal only)	Forward	No
	Reverse	Stops the machine at the same time as impact blow is detected.



4 modes

(Max/ Hard/ Med. / Soft for bolt)

1 T-mode

(for thin metal only)

One LED job light each on both sides

Light mode

- To turn on the light, set F/R change lever in the neutral position, then pull the switch trigger. To turn off the light, pull the switch trigger again.
- The light turns off automatically one hour after turned on.



Constant speed control

Allows to operate the tool at the same speed as that at which you operate the tool on a full charged battery, even when the remaining battery capacity becomes low.

Variable speed control by trigger

XPT

eXtreme Protection Technology

