



Cordless Circular Saw HS013G 415 mm (16-5/16")



40V^{LI-ION} max

Unveiling the world's largest 415 mm cordless circular saw*¹
Cuts through thick materials in a single stroke with high power similar to corded models

*1 As of August 2024



PRODUCT
DETAILS
Models and specs
may vary by country



Max cutting capacity
158 mm

Guide rule: optional accessory

Work amount

on a single full battery charge

Cut Melapi (Thickness: 150mm /
Width: 300mm / Bevel angle: 0° /
with BL4050F)

75 cuts



Comfortable cutting of thick materials with the high power similar to corded models




Lightweight design and enhanced maneuverability

The motor housing material has been changed from aluminum to resin, resulting in a weight reduction of 1.5kg compared with our AC model when a BL4050F battery is installed.

Lightweight
with BL4040
11.0 kg

Compact body

With the adoption of a BL motor, the width has been reduced by 65mm compared with our AC model, enhancing stability and maneuverability during blade changes.



Auto-start Wireless System

Part No. 199393-1

The wireless activation function enables clean and comfortable operation. By connecting the tool to a vacuum cleaner, you can run the cleaner automatically along with the switch operation of the tool. Wireless unit is compatible with all supported tools



eXtreme Protection Technology

Enhanced Dust and Drip-proof Performance ensure reliable operation even under bad weather



Accessories (optional)

TCT saw blade for circular saw

EFFICUT
415x35T
Part No. E-24832



Guide rule

Part No. 164019-4



Protect stand

(Standard equipment)
The resin stand allows for storage without damaging the tool.



Stabilizing the stand by pressing down the recessed portion with a foot allows for easy removal of the tool from storage.



The tool can be temporarily placed at an angle for easy access to the tool without bending over.



HS013GZ 415 mm (16-5/16")

Cordless Circular Saw

- High-power cutting of 6x timbers.
- Lightweight design and enhanced maneuverability.



Li-ion Ah 8.0 | 5.0 | 4.0
*Recommended batteries 4.0Ah (F), 5.0Ah, 8.0Ah
Not compatible with 2.0Ah & 2.5Ah batteries
40Vmax



Standard Equipment:
TCT Saw Blade, Hex Wrench, Joint, Protect Stand

• GZ: Without Charger & Battery



Blade Diameter	415 mm (16-5/16")
Max Cutting Capacity	0°: 158 mm (6-1/4") 45°: 106 mm (4-3/16")
No Load Speed (RPM)	2,100
Dimensions (L x W x H)	606 x 233 x 476 mm (23-7/8 x 9-1/8 x 18-3/4")
Net Weight	11.0 - 12.0 kg (24.3 - 26.5 lbs)
Work Amount (approx.)	75 cuts with BL4050F Melapi thickness 150 mm width 300 mm Bevel angle 0°

Like us on Facebook
MAKITA MALAYSIA

• Continuous Usage Time/ Work Amount: Actual performance may vary based on application. Items of standard equipment and specifications may vary by country or area. The weight and dimensions may differ depending on the attachment(s), including the battery cartridge. All pictures shown are for illustration purposes only.

12 MONTHS WARRANTY



Makita Power Tools (Malaysia) Sdn. Bhd. Co. Registration No.: 201301001778 (1031615-M)

HQ & Service Centre
Lot 824, Jalan Subang 5, Subang Industrial Area,
47500 Subang Jaya, Selangor.
Tel: 03-8023 0824 (General) | Fax: 03-8022 1448
03-8022 1443 (Service)

Johor (Johor Bahru) Service Centre
No. 12 & 14, Jalan Rosmerah 2/9,
Taman Johor Jaya,
81100 Johor Bahru, Johor.
Tel: 07-364 9406 | Fax: 07-364 9407

Sarawak (Kuching) Service Centre
Lot 1227, Lorong Demak Indah 2A,
Demak Laut Industrial Area, Phase 2A,
93050 Kuching Sarawak.
Tel: 082-496 800 | Fax: 082-496 900

Sabah (Kota Kinabalu) Service Centre
Lot 19, Jalan Buah Duku,
Kolombong Light Industrial Estate, Off Jalan Kolombong,
Kolombong Zone 1, 88450 Inanam, Kota Kinabalu, Sabah.
Tel: 088-388 278 | Fax: 088-388 279

www.makita.my
✉ makita@makita.my