makita®

Cordless Impact Driver TD004G

XGT

XGT 40V max Li-ion

Excellent fastening performance in heavy-duty tasks

Max fastening torque

230 N·m

Delivers excellent fastening performance in heavy-duty tasks, such as tightening hex head or hexalobular (star-shaped) hole head course thread screws, which are less prone to cam-out.

PRODUCT DETAILS
TD004G
Models and specs may vary by country

BL MOTOR XPT

Max fastening torque

230 N·m

- Delivers excellent fastening performance in heavy-duty tasks, such as tightening hex head or hexalobular (star-shaped) hole head course thread screws, which are less prone to cam-out.
- Capable of smoothly fastening screws on hard materials, such as LVL (Laminated Veneer Lumber)

4-stage impact power selection + T-mode (for thin metal sheets only)

- The impact power can be adjusted to four stages to match the type of screw and material.
- For tasks requiring attention to cam-out, such as with Phillips head screws, the impact force can be adjusted accordingly.
- Equipped with the T-Mode to minimize screw stripping, which is likely to occur when a self-drilling screw is tightened into a thin metal sheet workpiece under light load.



4-stage
4 (Max)
3 (Hard)
2 (Medium)
1 (Soft)

T-mode

BL MOTOR

The brushless motor provides longer work hours per charge and extended tool life.

One-touch bit installation
Reduced resistance allows for easier bit installation.

LED job light
Twin LEDs with preglow and afterglow functions

Variable speed control by trigger
Allows for speed adjustments based on the material or application.

Overall length
136 mm

Reversing switch

Soft grip

Hook

Accessories (optional)

Tool hanger set
Part No. 191K57-9

Drill chuck
Part No. 192173-4

XPT
eXtreme Protection Technology

TD004GZ

Cordless Impact Driver

40Vmax

*Recommended batteries
2.0Ah, 2.5Ah, 4.0Ah, 4.0Ah (F)

Standard Equipment:
Hook

• GZ: Without Charger & Battery

Capacity	Machine Screw: M4 - M8 (5/32 - 5/16") Standard Bolt: M5 - M20 (3/16 - 13/16") High Strength Bolt: M5 - M14 (3/16 - 9/16") Coarse thread (in length): 22 - 150 mm (7/8 - 5-7/8")
Hex Shank	6.35 mm (1/4")
No Load Speed (RPM)	Max: 0 - 3,900 I Hard: 0 - 3,000 Med.: 0 - 2,100 I Soft: 0 - 1,200
Impacts Per Minute (IPM)	Max: 0 - 3,900 I Hard: 0 - 3,600 Med.: 0 - 3,100 I Soft: 0 - 1,900
Max Fastening Torque	230 N·m (2,040 in.lbs.)
Dimensions (L x W x H)	136 x 86 x 248 mm (5-3/8 x 3-3/8 x 9-3/4")
Net Weight	1.8 - 3.1 kg (4.0 - 6.8 lbs.)
Work Amount (approx.)	113 pcs with BL4025 Hex head coarse thread screws 90 mm x 5.0 mm diameter into LVL (Laminated Veneer Lumber)

Like us on Facebook
MAKITA MALAYSIA

•Continuous Usage Time/ Work Amount: Actual performance may vary based on application. Items of standard equipment and specifications may vary by country or area. The weight and dimensions may differ depending on the attachment(s), including the battery cartridge. All pictures shown are for illustration purposes only.

12 MONTHS WARRANTY

Makita Power Tools (Malaysia) Sdn. Bhd. Co. Registration No.: 201301001778 (1031615-M)

HQ & Service Centre
Lot 824, Jalan Subang 5, Subang Industrial Area, 47500 Subang Jaya, Selangor.
Tel: 03-8023 0824 (General) I Fax: 03-8022 1448
03-8022 1443 (Service)

Johor (Johor Bahru) Service Centre
No.12 & 14, Jalan Rosmerah 2/9, Taman Johor Jaya, 81100 Johor Bahru, Johor.
Tel: 07-364 9406 I Fax: 07-364 9407

Sarawak (Kuching) Service Centre
Lot 1227, Lorong Demak Indah 2A, Demak Laut Industrial Area, Phase 2A, 93050 Kuching Sarawak.
Tel: 082-496 800 I Fax: 082-496 900

Sabah (Kota Kinabalu) Service Centre
Lot 19, Jalan Buah Duku, Kolombong Light Industrial Estate, Off Jalan Kolombong, Kolombong Zone 1, 88450 Inanam, Kota Kinabalu, Sabah.
Tel: 088-388 278 I Fax: 088-388 279

www.makita.my
makita@makita.my