



Cordless Driver Drill
Cordless Hammer Driver Drill
DDF484 13 mm (1/2") / DHP484 13 mm (1/2")



Durable Aluminum gear housing



Cordless Driver Drill
DDF484



Cordless Hammer Driver Drill
DHP484



High speed
2,000 min⁻¹



Aluminum gear housing and all metal gear construction

for extra-high transmission durability



Compact overall length
DDF484: 162 mm / DHP484: 172mm

21 Torque settings



Single sleeve keyless chuck

allows for easy bit installation/removal by one hand.

Capacity of drill chuck

DDF484: 1.5 - 13 mm (1/16 - 1/2")
DHP484: 13 mm (1/2")

Twin LED job light with preglow and afterglow functions



Powered by the following 18V Li-ion batteries

Variable speed control by trigger

Mechanical 2-speed gearing



Best possible ergonomic handle with soft grip for driver-drill applications

- In order to provide maximum thrust to the bit, the top back of the handle is ergonomically contoured and widened to perfectly fit the U-shape formed between user's thumb and index finger.
- Newly designed slimmer grip provides comfortable grip with less fatigue.

Belt clip



**Cordless Driver Drill
DDF484**



**Cordless Hammer Driver Drill
DHP484**



DDF484Z 13 mm (1/2")

Cordless Driver Drill

18V



Standard Equipment:
Belt Clip, (+)(-) Bit

• Z : Without Charger, Battery & Carrying Case



DHP484RME | DHP484RFX6 | DHP484Z 13 mm (1/2")

Cordless Hammer Driver Drill

18V



Accessories set for DHP484RFX6



Standard Equipment:
Belt Clip, (+)(-) Bit

- RME : 1x Rapid Charger, 2x 4.0Ah Battery
- RFX6 : 1x Rapid Charger, 2x 3.0Ah Battery, Accessories Set, Carrying Case
- Z : Without Charger, Battery & Carrying Case



Capacity	Steel: 13 mm (1/2") Wood: 38 mm (1-1/2")
Chuck Capacity	1.5 - 13 mm (1/16 - 1/2")
No Load Speed (RPM)	High: 0 - 2,000 Low: 0 - 500
Max Fastening Torque	Hard: 54 N-m (480 in lbs) Soft: 30 N-m (270 in lbs)
Max Torque	65 N-m (580 in lbs)
Dimensions (L x W x H)	172 x 79 x 261 mm (6-3/4 x 3-1/8 x 10-1/4")
Net Weight	1.5 - 1.8 kg (3.3 - 4.0 lbs)
Work Amount (approx.)	1550 holes with BL1850B Wood bit Ø 9 mm (30 mm thick Luan)

Capacity	Steel: 13 mm (1/2") Wood: 38 mm (1-1/2") Masonry: 13 mm (1/2")
Chuck Capacity	1.5 - 13 mm (1/16 - 1/2")
Impacts Per Minute (IPM)	High: 0 - 30,000 Low: 0 - 7,500
No Load Speed (RPM)	High: 0 - 2,000 Low: 0 - 500
Max Fastening Torque	Hard: 54 N-m (480 in lbs) Soft: 30 N-m (270 in lbs)
Max Torque	65 N-m (580 in lbs)
Dimensions (L x W x H)	182 x 79 x 261 mm (7-1/8 x 3-1/8 x 10-1/4")
Net Weight	1.6 - 1.9 kg (3.5 - 4.2 lbs)
Work Amount (approx.)	1850 pcs with BL1850B Wood Screw Ø 9 x 25 mm

Makita Power Tools (Malaysia) Sdn. Bhd. Co. Registration No.: 201301001778 (1031615-M)

HQ & Service Centre

Lot 824, Jalan Subang 5, Subang Industrial Area,
47500 Subang Jaya, Selangor.
Tel: 03-8023 0824 (General) | Fax: 03-8022 1448
03-8022 1443 (Service)

Johor (Johor Bahru) Service Centre

No.12 & 14, Jalan Rosmerah 2/9,
Taman Johor Jaya,
81100 Johor Bahru, Johor.
Tel: 07-364 9406 | Fax: 07-364 9407

Sarawak (Kuching) Service Centre

Lot 1227, Lorong Demak Indah 2A,
Demak Laut Industrial Area, Phase 2A,
93050 Kuching Sarawak.
Tel: 082-496 800 | Fax: 082-496 900

Sabah (Kota Kinabalu) Service Centre

Lot 19, Jalan Buah Duku,
Kolombong Light Industrial Estate, Off Jalan Kolombong,
Kolombong Zone 1, 88450 Inanam, Kota Kinabalu, Sabah.
Tel: 088-388 278 | Fax: 088-388 279

FOLLOW MAKITA MALAYSIA:



www.makita.my