



Cordless Area Worklight ML010G 40Vmax, 18V, 14.4V / AC

XGT

40V^{Li-ion}max

18V^{Li-ion}
LITHIUM-ION



**PRODUCT
DETAILS**
Models and specs
may vary by country

**Improved Self-righting
performance**



**Up to 4 batteries can be installed in
parallel.**

two LXT batteries + two XGT batteries



Continuous run time (approx)

Low mode **59 hours**

Battery: BL4080F x2 & BL1860B x2
all LEDs light up



Max luminous flux

5,500 lm



XPT

Compatible with 3 power sources



AC



two in parallel or one



two in parallel or one



Inlet type AC power supply cord

3 brightness settings

with memory function of the setting last time you power off




Low

1,500 lm



Medium

3,000 lm



High

5,500 lm

Lighting area selection



left
180°



360°



right
180°

Continuous run time (approx)

all LEDs light up

Battery	High	Medium	Low
BL1860B x2	4.5 h	8.5 h	16 h
BL4040 x2	6.5 h	11 h	21 h
BL4050F x2	8.5 h	14 h	27 h
BL4040 x2 + BL1860B x2	11 h	19.5 h	37 h
BL4050F x2 + BL1860B x2	13 h	22.5 h	43 h
BL4080F x2	13 h	23 h	43 h
BL4080F x2 + BL1860B x2	17.5 h	-	59 h

Battery capacity warning function



Hook for power cord



Battery fuel gauge



Padlock hole anti-battery theft



AC outlet allows for connecting up to 8 units of this light together.



IP54-rated water resistance (Only with DC power supply)



ML010G (MYAML010G)

Cordless Area Worklight

• Self-righting design won't fall over even if tilted up to 80 degrees.



*Recommended batteries (40Vmax)
2.0Ah, 2.5Ah,
4.0Ah, 4.0Ah (F),
5.0Ah, 8.0Ah

Improved Self-righting performance



Standard Equipment:
Power supply cord UK plug

• Without Charger & Battery

XPT

Luminous Flux	High: 5,500 lm Med.: 3,000 lm Low: 1,500 lm
Illuminance	High 550 lx Med 300 lx Low 150 lx at 1 m from the light source High 70 lx Med 40 lx Low 20 lx at 3 m from the light source High 25 lx Med 15 lx Low 7 lx at 5 m from the light source
Dimensions (L x W x H)	490 x 490 x 814 mm (19-1/4 x 19-1/4 x 32")
Net Weight	14.4 - 19.2 kg (31.7 - 42.3 lbs)
Continuous Usage Time (approx.)	59 hrs all LEDs light up in low mode with BL4080F x2 & BL1860B x2

Follow us on Facebook
MAKITA MSIA

*Continuous Usage Time/ Work Amount: Actual performance may vary based on application. Items of standard equipment and specifications may vary by country or area. The weight and dimensions may differ depending on the attachment(s), including the battery cartridge. All pictures shown are for illustration purposes only.

Makita Power Tools (Malaysia) Sdn. Bhd. Co. Registration No.: 201301001778 (1031615-M)

HQ & Service Centre

Lot 824, Jalan Subang 5, Subang Industrial Area,
47500 Subang Jaya, Selangor
Tel: 03-8023 0824 (General) | Fax: 03-8022 1448
03-8022 1443 (Service)

Johor (Johor Bahru) Service Centre

No. 12 & 14, Jalan Rosmerah 2/9,
Taman Johor Jaya,
81100 Johor Bahru, Johor.
Tel: 07-364 9406 | Fax: 07-364 9407

Sarawak (Kuching) Service Centre

Lot 1227, Lorong Demak Indah 2A,
Demak Laut Industrial Area, Phase 2A,
93050 Kuching Sarawak.
Tel: 082-496 800 | Fax: 082-496 900

Sabah (Kota Kinabalu) Service Centre

Lot 19, Jalan Buah Duku,
Kolombong Light Industrial Estate, Off Jalan Kolombong,
Kolombong Zone 1, 88450 Inanam, Kota Kinabalu, Sabah.
Tel: 088-388 278 | Fax: 088-388 279

12 MONTHS WARRANTY



www.makita.my
makita@makita.my