



**Cordless Breaker
HM004G**



28.6 28.6mm Hex
Shank Type

40V^{Li-ion}max + **40V^{Li-ion}max**



XGT X2
80V^{max}

High power similar to corded models



Impact energy
72.8 Joule

Low Vibration
6.5 m/s²

 
**PRODUCT
DETAILS**
HM004G
Models and specs
may vary by country

XGT X2
80Vmax



40Vmax Li-ion + 40Vmax Li-ion

Powered by two 40Vmax XGT
Li-Ion batteries in series
(80Vmax)

BL
MOTOR

High power
brushless
motor

Impact energy
72.8 Joule



AWS

(Auto-start Wireless System)

Connects to compatible vacuum cleaner with Bluetooth.
The vacuum cleaner automatically runs while the switch is on.


Bluetooth



Accessories (optional)
Dust extractor attachment set

w/o hose
Part No. 197168-2

w/ hose
Part No. 197148-8



Low Vibration thanks to **AVT**


(Anti-Vibration Technology)

Vibration level **6.5 m/s²**

Active dynamic vibration absorber moves in the opposite direction to the drive piston to reduce vibration.

Vibration absorbing housing

provides a practical combination of high power and low vibration.



Vibration absorbing spring (4 places)

Counter weight mechanism

reduces vibration during chipping operation.



Main power switch
Battery capacity warning lamp



Maintenance warning lamp

LED job light

Twin LEDs with preglow and afterglow functions



SOFT NO LOAD

Suppression of motor speed during no-load



During no-load



Under load

Slim body for excellent visibility

219mm



Hex shank: 28.6mm

Self sharpening bull point

XPT

(eXtreme Protection Technology)



HM004GZ05

Cordless Breaker

• High power similar to corded models.

Standard Equipment:

Hex Wrench, Self-Sharpening Bull Point (B-10372)

• GZ05: Without Charger & Battery



BL **AVT** **AWS** **SOFT NO LOAD** **XPT**



Li-ion Ah 8.0 5.0 4.0

*Recommended batteries
4.0Ah, 4.0Ah (F),
5.0Ah, 8.0Ah

40Vmax x2



Impact Energy 72.8 J (53.7 ft.lbs.)

Blows Per Minute (BPM) 870

Shank Diameter Hex 28.6 mm (1-1/8")

Dimensions (L x W x H) 882 x 227 x 540 mm
(34-3/4 x 8-15/16 x 21-1/4")

Net Weight (with battery) 29.7 - 32.1 kg (65.5 - 70.8 lbs)

Work Amount (approx.) 946 kg with BL4080F x 2
Concrete 1000 x 800 x 300 mm chipped
Grade 40
or 20 min continuous usage

Like us on Facebook
MAKITA MALAYSIA

• Continuous Usage Time/ Work Amount: Actual performance may vary based on application. Items of standard equipment and specifications may vary by country or area. The weight and dimensions may differ depending on the attachment(s), including the battery cartridge. All pictures shown are for illustration purposes only.

12 MONTHS WARRANTY



www.makita.my
makita@makita.my

Makita Power Tools (Malaysia) Sdn. Bhd. Co. Registration No.: 201301001778 (1031615-M)

HQ & Service Centre

Lot 824, Jalan Subang 5, Subang Industrial Area,
47500 Subang Jaya, Selangor
Tel: 03-8023 0824 (General) | Fax: 03-8022 1448
03-8022 1443 (Service)

Johor (Johor Bahru) Service Centre

No.12 & 14, Jalan Rosmerah 2/9,
Taman Johor Jaya,
81100 Johor Bahru, Johor.
Tel: 07-364 9406 | Fax: 07-364 9407

Sarawak (Kuching) Service Centre

Lot 1227, Lorong Demak Indah 2A,
Demak Laut Industrial Area, Phase 2A,
93050 Kuching Sarawak.
Tel: 082-496 800 | Fax: 082-496 900

Sabah (Kota Kinabalu) Service Centre

Lot 19, Jalan Buah Duku,
Kolombong Light Industrial Estate, Off Jalan Kolombong,
Kolombong Zone 1, 88450 Inanam, Kota Kinabalu, Sabah.
Tel: 088-388 278 | Fax: 088-388 279