



Cordless Angle Impact Wrench DTL300 / DTL302



For automotive maintenance

Max fastening torque
340 N·m
6 seconds after seating,
when tightening

Nut-busting torque
530 N·m
within 3 seconds,
when loosening

High power & High-speed fastening

Suitable for tight spaces in vehicle and farm equipment maintenance



For tractor tine replacement



For railway maintenance work

■ DTL300



12.7[1/2"]
C ring
with hole



DTL300



PRODUCT
DETAILS
Models and specs
may vary by country

■ DTL302



9.5[3/8"]
C ring
without hole



DTL302



PRODUCT
DETAILS
Models and specs
may vary by country



High power & High-speed fastening

Slim body for tight spaces with high-power fastening



Auto-stop system in forward/reverse rotation modes

For continuous temporary fastening and preventing nuts from falling off during loosening



	Description	Application
Forward	Rotates in soft impact mode and stops immediately after impact starts.	Temporary fastening of bolts and nuts
Reverse	Rotates in hard impact mode and stops immediately after impact ends.	Preventing nut loss when loosening bolts and nuts

3-stage impact power selection



Mode	Max blows
Hard	4,000min ⁻¹
Medium	2,800min ⁻¹
Soft	1,800min ⁻¹



LED job light
3 brightness levels



Excellent maneuverability

The center of gravity is close to the switch, minimizing hand fatigue.



Slim Grip
115 mm circumference on the little finger side

Accessories (optional)

Protector

Part No. 422C91-3

Protects from dust, dirt, and corrosion.



DTL300Z 12.7 mm (1/2")

Cordless Angle Impact Wrench

18V



* Z: Without Charger & Battery



Fastening Capacities	Standard Bolt: M10 - M20 (3/8 - 3/4") High Strength Bolt: M10 - M16 (3/8 - 5/8")
Square Drive	12.7 mm (1/2")
No Load Speed (RPM)	Hard: 0 - 3,200 Medium: 0 - 1,500 Soft: 0 - 1,000
Impacts Per Minute (IPM)	Hard: 0 - 4,000 Medium: 0 - 2,800 Soft: 0 - 1,800
Max Fastening Torque	310 - 340 N·m (230 - 250 ft lbs)
Nut-Busting Torque	500 - 530 N·m (370 - 390 ft lbs)
Dimensions (L x W x H)	396 - 414 x 80 x 86 - 92 mm (15-5/8 - 16-1/4 x 3-1/8 x 3-3/8 - 3-5/8")
Net Weight	1.8 - 2.1 kg (4.0 - 4.6 lbs)

DTL302Z 9.5 mm (3/8")

Cordless Angle Impact Wrench

18V



* Z: Without Charger & Battery



Fastening Capacities	Standard Bolt: M10 - M20 (3/8 - 3/4") High Strength Bolt: M10 - M16 (3/8 - 5/8")
Square Drive	9.5 mm (3/8")
No Load Speed (RPM)	Hard: 0 - 3,200 Medium: 0 - 1,500 Soft: 0 - 1,000
Impacts Per Minute (IPM)	Hard: 0 - 4,000 Medium: 0 - 2,800 Soft: 0 - 1,800
Max Fastening Torque	310 - 340 N·m (230 - 250 ft lbs)
Nut-Busting Torque	500 - 530 N·m (370 - 390 ft lbs)
Dimensions (L x W x H)	396 - 414 x 80 x 86 - 92 mm (15-5/8 - 16-1/4 x 3-1/8 x 3-3/8 - 3-5/8")
Net Weight	1.8 - 2.1 kg (4.0 - 4.6 lbs)

Makita Power Tools (Malaysia) Sdn. Bhd. Co. Registration No.: 201301001778 (1031615-M)

HQ & Service Centre

Lot 824, Jalan Subang 5, Subang Industrial Area,
47500 Subang Jaya, Selangor.
Tel: 03-8023 0824 (General) | Fax: 03-8022 1448
03-8022 1443 (Service)

Johor (Johor Bahru) Service Centre

No.12 & 14, Jalan Rosmerah 2/9,
Taman Johor Jaya,
81100 Johor Bahru, Johor.
Tel: 07-364 9406 | Fax: 07-364 9407

Sarawak (Kuching) Service Centre

Lot 1227, Lorong Demak Indah 2A,
Demak Laut Industrial Area, Phase 2A,
93050 Kuching Sarawak.
Tel: 082-496 800 | Fax: 082-496 900

Sabah (Kota Kinabalu) Service Centre

Lot 19, Jalan Buah Duku,
Kolombong Light Industrial Estate, Off Jalan Kolombong,
Kolombong Zone 1, 88450 Inanam, Kota Kinabalu, Sabah.
Tel: 088-388 278 | Fax: 088-388 279

FOLLOW MAKITA MALAYSIA:



www.makita.my