



Cordless Impact Wrench DTW1005



High power and long anvil with 19mm (3/4") square drive

Max fastening torque

1,360^{*} N·m

The maximum fastening torque
at 6 seconds after seating

Nut-Busting torque

1,700^{}** N·m

at max impact mode (4)



*When tightening an M30 friction grip bolt

**The maximum torque value at which an M33 friction grip bolt can be loosened within 3 seconds.



Suitable for loosening and tightening bolts and nuts in recessed areas



BL MOTOR
High power BL Motor



Constant speed control
Ensures stable torque until the end of the battery capacity.
(Except the reverse and max forward rotations)

XPT
eXtreme Protection Technology



Electronic 4-stage impact power selection

enables user to control the power and speed depending on the applications.



Mode	No load speed (min ⁻¹)	Impacts per minutes (min ⁻¹)
1. Soft	0-800	-
2. Med.	0-900	0-1,600
3. Hard	0-1,000	0-1,800
4. Max.	0-1,800	0-2,200

Full speed mode
Allows the tool to reach full speed with fewer trigger pull, minimizing fatigue during continuous work.

Accessories (optional) Extension handle set

Part No. 191G67-2



Mode settings suitable for removing and installing tires, etc.

Mode	Behavior of the tool (Work example)	Target fastening torque	Reverse
1. Soft	Stops immediately after seating (Manual tightening of large truck tires) with Auto-stop	30 - 50 N-m*	Rotates slowly after finishing impacts, with Auto-stop
2. Med.	Stops approx. 0.3 seconds after seating (Initial tightening of large truck tires) with Auto-stop	50 - 150 N-m*	
3. Hard	Stops approx. 0.5 seconds after seating (Temporary tightening of large truck tires) with Auto-stop	300 - 450 N-m*	
4. Max.	Tightens at the maximum speed	1,360 N-m**	Loosens at the maximum speed

*With M20 - M24 bolts **At 6 seconds after seating, with an M30 friction grip bolt

DTW1005ZX1 19 mm (3/4")

Cordless Impact Wrench

High power and the long anvil, it is suitable for loosening and tightening bolts and nuts in recessed areas such as the rear wheels of trucks.



18V



Forward/Reverse Rotation
Auto Stop Mode



C ring

Standard Equipment:
Hook, Shoulder Belt

• ZX1: Without Charger & Battery



Square Drive	19.0 mm (3/4")
Anvil Length	137 mm (5-3/8")
No Load Speed (RPM)	Max: 0 - 1,800 Hard: 1,000 Mid: 900 Soft: 800
Impacts Per Minute (IPM)	Max: 0 - 2,200 Hard: 1,800 Mid: 1,600 Soft: N/A
Max Fastening Torque	6-sec tightening: 1,360 N-m (1,000 ft.lbs.) 3-sec tightening: 1,150 N-m (N/A ft.lbs.)
Nut-Busting Torque	1,700 N-m (1,250 ft.lbs.)
Dimensions (L x W x H)	339 x 91 x 291 mm (13-3/8 x 3-5/8 x 11-1/2")
Net Weight (with battery)	3.9 - 4.2 kg (8.6 - 9.3 lbs.)

Like us on Facebook
MAKITA MALAYSIA

• Continuous Usage Time/ Work Amount: Actual performance may vary based on application. Items of standard equipment and specifications may vary by country or area. The weight and dimensions may differ depending on the attachment(s), including the battery cartridge. All pictures shown are for illustration purposes only.

12 MONTHS WARRANTY

Makita Power Tools (Malaysia) Sdn. Bhd. Co. Registration No.: 201301001778 (1031615-M)

HQ & Service Centre

Lot 824, Jalan Subang 5, Subang Industrial Area,
47500 Subang Jaya, Selangor.
Tel: 03-8023 0824 (General) | Fax: 03-8022 1448
03-8022 1443 (Service)

Johor (Johor Bahru) Service Centre

No. 12 & 14, Jalan Rosmerah 2/9,
Taman Johor Jaya,
81100 Johor Bahru, Johor.
Tel: 07-364 9406 | Fax: 07-364 9407

Sarawak (Kuching) Service Centre

Lot 1227, Lorong Demak Indah 2A,
Demak Laut Industrial Area, Phase 2A,
93050 Kuching Sarawak.
Tel: 082-496 800 | Fax: 082-496 900

Sabah (Kota Kinabalu) Service Centre

Lot 19, Jalan Buah Duku,
Kolombong Light Industrial Estate, Off Jalan Kolombong,
Kolombong Zone 1, 88450 Inanam, Kota Kinabalu, Sabah.
Tel: 088-388 278 | Fax: 088-388 279



www.makita.my
✉ makita@makita.my