

Foldable into a compact size for simple storage and transport



Push the unlock button to expand / fold the tripod base



Shoulder belt
Attachable to the worklight or tool bag for comfortable carrying of the worklight



Cordless Worklight
DML813 | DML814


IP55
certified weather
and dust resistance

Max luminous flux
3,000 lm
Max height
2,240 mm

DML813 (MYADML813)

Cordless Worklight

• LED color is daylight white, which is similar to the natural light and ideal for working spaces



18V



Spot lighting



Luminous Flux	High: 3,000 Mid: 1,700 Low: 900lm
Illuminance	at 1m from the light source: High: 1,250 Mid: 750 Low: 400lx at 3m from the light source: High: 130 Mid: 80 Low: 40lx at 5m from the light source: High: 50 Mid: 30 Low: 15lx
Lighting Coverage	Front: 4.5m Sides: 5.3m
Dimensions (L x W x H)	Folding Position: 260x216x1,000mm (10-1/4x8-1/2x39-3/8") Operating Position (Max Height): 573x658x1,250 - 2,240mm (22-1/2x26x49-1/4-88")
Net Weight	7.2-7.9kg (15.9-17.4lbs.)
Continuous Usage Time (approx.)	Low: 10 hrs Med: 5.5 hrs High: 3 hrs with BL1850B

Standard Equipment:
Shoulder Belt, Tool Bag

• Without Charger & Battery


DML814 (MYADML814)

Cordless Worklight

• LED color is daylight white, which is similar to the natural light and ideal for working spaces



Spot lighting



Area lighting



Luminous Flux	High: 3,000 Mid: 1,700 Low: 900 lm
Illuminance	at 1m from the light source: High: 1,250 Mid: 750 Low: 400 lx at 3m from the light source: High: 130 Mid: 80 Low: 40 lx at 5m from the light source: High: 50 Mid: 30 Low: 15 lx
Lighting Coverage	Front: 4.7m Sides: 5.6m
Dimensions (L x W x H)	Folding Position: 260x216x1,000mm (10-1/4x8-1/2x39-3/8") Operating Position (Max Height): 573x658x1,250 - 2,240mm (22-1/2x26x49-1/4-88")
Net Weight	7.4 - 8.1kg (16.3 - 17.9lbs.)
Continuous Usage Time (approx.)	Low: 10 hrs Med: 5.5 hrs High: 3 hrs with BL1850B

Standard Equipment:
Shoulder Belt, Tool Bag

• Without Charger & Battery

Like us on Facebook
MAKITA MALAYSIA

• Continuous Usage Time/ Work Amount: Actual performance may vary based on application. Items of standard equipment and specifications may vary by country or area. The weight and dimensions may differ depending on the attachment(s), including the battery cartridge. All pictures shown are for illustration purposes only.

Makita Power Tools (Malaysia) Sdn. Bhd. Co. Registration No.: 201301001778 (1031615-M)

HQ & Service Centre
Lot 824, Jalan Subang 5, Subang Industrial Area,
47500 Subang Jaya, Selangor.
Tel: 03-8023 0824 (General) | Fax: 03-8022 1448
03-8022 1443 (Service)

Johor (Johor Bahru) Service Centre
No.12 & 14, Jalan Rosmerah 2/9,
Taman Johor Jaya,
81100 Johor Bahru, Johor.
Tel: 07-364 9406 | Fax: 07-364 9407

Sarawak (Kuching) Service Centre
Lot 1227, Lorong Demak Indah 2A,
Demak Laut Industrial Area, Phase 2A,
93050 Kuching Sarawak.
Tel: 082-496 800 | Fax: 082-496 900

Sabah (Kota Kinabalu) Service Centre
Lot 19, Jalan Buah Duku,
Kolombong Light Industrial Estate, Off Jalan Kolombong,
Kolombong Zone 1, 88450 Inanam, Kota Kinabalu, Sabah.
Tel: 088-388 278 | Fax: 088-388 279



www.makita.my
✉ makita@makita.my



DML813
[Spot lighting]



DML814
[Spot lighting]



[Area lighting]





2,240 mm



The height of light head can be adjusted steplessly



1,250 mm

Battery capacity warning function
automatically notifies the user about reduction in battery capacity with the decrease of illuminance (only one LED is on for notification).



DML813 ▶

◀ DML814




Padlock hole for battery theft protection
*Padlock not included

Easy installation and removal of battery
The battery port is located at the middle height of the worklight so that the user need not bend down to access the battery.



Three hook holes for the shoulder belt
Two hook holes are located on the carrying handle beside the battery, and one on the end of a tripod leg.

Tripod fixing hole
The tripod can be firmly secured to the ground with a screw or peg



Continuous Usage Time

with BL1850B (approx.)

High 3 h	Medium 5.5 h	Low 10 h
--------------------	------------------------	--------------------

3 Brightness settings

High 3,000 lm	Medium 1,700 lm	Low 900 lm
-------------------------	---------------------------	----------------------

Pivoting range of light head for spot lighting



right and left
115°



up and down
110°

Pivoting range of 3 small light heads for area lighting



up and down (DML814 only)
90°